COLORADO DEPARTMENT OF TRANSPORTATION

PRE-APPROVED PRODUCT EVALUATION REQUEST & SUMMARY

APL Reference No. 2786-10

Product Evaluation Coordinator
Colorado Department of Transportation
4670 North Holly Street, Unit A
Denver, Colorado 80216

Material code: 401.09.01.00

FOR INTERNAL CDOT USE

Material code description full name: Bituminous Mixtures, Release Agent

PART 1

Product name: Enviro-Slide Ultra	Product category: Asphalt\Asphalt Release Agent\Truck Beds Only
Product representative (name & address): Attn: Maurice Slayden Rhomar Industries, Inc. 2107 E Rockhurst St Springfield, MO 65802 Phone: 417-866-5592 FAX: 417-866-5593	Manufacturer (name & address): Attn: Maurice Slayden Rhomar Industries, Inc. 2107 E Rockhurst St Springfield, MO 65802 Phone: 417-866-5592 FAX: 417-866-5593
Web-site address: www.rhomar.com	Web-site address: www.rhomar.com

Description of the product: (Include specific quantifiable details from tech data sheet. Advertising generalities are not appropriate.)

ENVIRO-SLIDE Ultra is a synthetic polymer release agent designed specifically to address the demands of SuperPave asphalt mixes such as SMA, OGFC or fibered mixes. An asphalt release agent that will prevent asphalt from sticking to the bed of trucks without degrading the asphalt. Will not strip the oil from the asphalt, thus compromising the integrity of the whole load.

APPROVED FOR TRUCK BEDS ONLY. APPROVED DILUTION RATE OF 10:1 for CDOT.

Restrictions, (installation and/or use):

APPROVED FOR TRUCK BEDS ONLY. APPROVED DILUTION RATE OF 10:1 for CDOT.

Use of the product, (be specific to CDOT highway activities only):

Release agent to be used in truck beds

Benefits to CDOT, (how will your product enhance quality, improve safety, save money, be a better value then other manufacturer's products):

ENVIRO-SLIDE Ultra is 100% biodegradable, non-flammable.
ENVIRO-SLIDE Ultra contains no petroleum hydrocarbons which strip the oils from the aggregate.
ENVIRO-SLIDE Ultra releases all types of asphalt, even the super-sticky polymer modified mixes.
ENVIRO-SLIDE Ultra dilutes up to 40:1 which offers savings for the Colorado DOT

Specifications, (listing those applicable is required) **& Certificate of Compliance** (required to certify compliance with listed specifications):

- ☐ CDOT :
- ☐ ASTM :
- ☐ AASHTO :
- ☐ FHWA :
- ☒ other : TX DOT Evaluated and accepted per CDOT requirements.

Product testing, (from national/independent laboratories or universities) **& Certified Test Report** (CTR required to validate all claims):

- ☐ NTPEP-AASHTO :
- ☐ FHWA :
- ☒ other : TX DOT
- ☒ other : Synthetics Solutions, Inc. (February 10, 2010)

State DOT Approvals, (current documentation required):

Texas

Sample submitted: ☐ yes ☒ no ☐ n/a | Materials Safety Data Sheets (MSDS): ☒ yes ☐ no ☐ n/a

Notes/Additional Comments