



COLORADO
Department of Transportation
Division of Maintenance & Operations

Intersection Control Assessment Tool (ICAT)

VERSION 1.0 – SEPTEMBER 24, 2021

Agenda

- Description of ICAT and why it was developed by CDOT
- The goals and benefits of ICAT
- Walk-through guide of each worksheet
 - Introduction Data
 - Stage 1 Shortlist
 - Stage 2 Assessment
- Use of an example case study to illustrate tool functionality

What is ICAT?

- CDOT's Intersection Control Assessment Tool (ICAT)
 - Data-driven, performance-based approach
 - Objectively screen multiple alternatives
 - Identify optimal intersection control
- Support Colorado's safety policies and procedures
 - Traceability, transparency, consistency, and accountability when selecting an intersection type
 - Shift away from wider/larger intersections & signalization
 - Mainstream proven innovative and underutilized strategies
 - Emphasize context sensitivity, cost-effectiveness and sustainability

Why ICAT?

- Highway Safety Improvement Program: Focus on areas with greatest potential to improve safety, including:
 - Intersection safety
 - Quantitative analysis to select intersection control
 - Consider context-sensitive control strategies
 - Consider project life cycle costs (not just capital costs)
 - Safe facilities for all users with overall best value
 - Evaluation of multiple alternatives using quantitative analysis
 - Documentation to support control decision

Why ICAT?

- Ensure intersection investments across the state are prioritized
- Defensible benefits for safety and operations
- Provide simplified and consistent use of data to assess and quantify intersection control improvement benefits

Benefits of ICAT



Simplified, consistent way to use data to quantify & evaluate intersection control



Reduces time to analyze & compare multiple alternatives



Provide traceability, transparency, consistency and accountability when evaluating and selecting control types




Serves as agreed upon decision document in the planning process

Getting Started

- ICAT is open-source Excel workbook that includes 7 worksheets:
 - **Introductions and Intersections:** Purpose and goals, tool processes and responsibilities descriptions and graphics of intersection types and publication links
 - **Intersection Data:** Roadway, intersection, control, safety and traffic data entry
 - **Stage I:** Screening to eliminate alternatives and advance shortlist
 - **Costs and Stage II:** Generate cost estimates, assess shortlisted alternatives and select preferred alternative
 - **Environmental Impacts:** Document environmental mitigation needed
- Computations rely on input from multiple worksheets - no results should be considered final until all worksheets are fully complete

Getting Started

- Several tools provided to assist tool data entry:
 - ICAT Users Guide – provides step by step process for entering data
 - Data Entry Checklist – provides checklist for all data needed and entered in ICAT



CDOT INTERSECTION CONTROL ASSESSMENT TOOL (ICAT)

Version 1.0 Users Guide

The CDOT Intersection Control Assessment Tool (ICAT) is an open-source Excel workbook that includes seven (7) worksheets, each containing information and data inputs to complete an intersection control assessment. Note, computations may rely on input from multiple worksheets, and the analysis results are continually updated as the worksheets are completed. Therefore, no results should be considered final until all worksheets are fully complete.

INTRODUCTION WORKSHEET

The *Introduction* worksheet provides information on the purpose and goals of the intersection control assessment, a description of the tool processes and responsibilities, answers to frequently asked questions, and documentation of ICAT version updates.


INTERSECTIONS WORKSHEET


The *Intersections* worksheet provides descriptions and graphics of each intersection type included for evaluation and links to national publications that describe each intersection type in greater detail.

INTERSECTION DATA WORKSHEET

The *IntersectionData* worksheet begins the ICAT data entry process. **Figure 1** illustrates a blank worksheet and requested inputs for project, traffic, and safety data. Here and throughout the tool, orange text or boxes indicate **required** data inputs, and blue text or text boxes indicate

Figure 1: Blank *IntersectionData* Worksheet





CDOT ICAT: User Testing Guidelines and Checklist

Developed and Maintained in Cooperation with Georgia DOT

CDOT ICAT Version 1.0 | Release Date: 3/30/2021

Instructions:

1. Using own Test Case example and data, input information into the ICAT and check appropriate check-boxes in the input checklist below when complete.
2. Take screen shots at the incremental steps listed below to ensure complete data entry and to assist with troubleshooting.
3. If an issue is identified, include a screen shot and supporting details in the additional tabs provided. Duplicate the tabs if multiple issues are identified.
4. Once the checklist and ICAT are completed, upload to your Region folder in the Google Drive link provided.

Note: The ICAT must be opened in Excel, not Google Sheets

Input Checklist:

"IntersectionData" Tab:

- County
- CDOT Region
- Major Street: Name, Typical Section, ROW, Roadway Classification, Turn Lanes at Intersection, and Speed
**Note that without inputting Intersection Turn Lanes, user may get error message in future tabs*
- Minor Street: Name, Typical Section, ROW, Roadway Classification, Turn Lanes at Intersection, and Speed
**Note that without inputting Intersection Turn Lanes, user may get error message in future tabs*
- Major Road Direction, Area Type, Existing Intersection Control, and Terrain
- Update Existing, Opening, and Design Project Traffic Year; If future volumes are unknown, include Annual Growth Rate and K Factor
- Input existing traffic volumes, truck percentages, and pedestrians; if known, input future traffic information

Introduction

- Summarizes tool goal and requirements
- Introduces two-phase process and roles and responsibilities
- Link to ICAT Users Guide
- Track future versions and program updates



About the Colorado ICAT:

Introduction: The Intersection Control Assessment Tool (ICAT) uses a data-driven, performance-based approach to objectively screen alternatives and identify an optimal geometric and control solution for an intersection. In 2015, Colorado Governor Hickenlooper announced Colorado's safety initiative to reduce transportation related deaths: Moving Colorado Towards Zero Deaths. Zero deaths and serious injuries is a core value of the state's Strategic Transportation Safety Plan, which provides innovative and data-driven approaches to improving highway safety. Colorado's ICAT was developed to ensure intersection investments across the state are prioritized and implemented with defensible benefits for safety and operations.

Tool Goal: The goal of ICAT is to provide a simplified and consistent way of importing traffic, safety, cost, environmental impact and stakeholder data to assess and quantify intersection control improvement benefits. The tool supports Colorado's stated policies and procedures to provide traceability, transparency, consistency and accountability when identifying and selecting an intersection control solution that both meets project purpose and reflects overall best value in terms of specific performance-based criteria. Note that a PDF of the ICAT users guide is available on both this tab (right) and the IntersectionData tab.

Requirements: Use of ICAT shall be required for any intersection or ramp termini improvement (new intersection, intersection modification, widening/reconstruction corridor project, or work requiring an access permit that affects an intersection) when: **1)** The intersection includes at least one roadway designated as a State Highway or part of the NHS, **2)** The intersection will be designed or constructed using State or Federal funding, **3)** The intersection is included in Access Control Plans (ACP), Planning and Environmental Linkages (PEL), Corridor Planning Studies, or Traffic Impact Studies (TIS), or **4)** Requested by the Regional Traffic Representative's (RTR). Use of ICAT shall NOT be required when the proposed work does not include any geometric or capacity changes to the intersection design such as (but not limited to): resurfacing pavement projects, striping projects, routine maintenance projects, traffic signal retiming projects (that do not include adding a phase), a proposed RIRO intersection that meets the Colorado State Highway Access Code, or signal maintenance projects (to upgrade deficient equipment). A waiver eligibility form must be completed by the Project Manager and submitted to the RTR, and if approved, the project shall be exempt from ICAT requirements.

Two-Stage The assessment process consists of two stages: Stage 1, a Screening Analysis and Stage 2, Alternative Selection. The intent of Stage 1 is to eliminate any **Process:** infeasible intersection types through a series of screening questions. The purpose of Stage 2 is to perform a detailed analysis to determine a preferred alternative selection. The ICAT forms are designed to minimize required data inputs using drop-down menu choices and limiting text entry. All fields shaded in orange require either data entry or drop-down menu choices, and data fields in all worksheets must be filled before any reliable results can be obtained. All non data-entry cells in worksheets are locked, and all worksheets are password protected.

Stage 1: Stage 1 is intended to screen many different intersection types and select between 2 and 5 alternatives for detailed analysis in Stage 2. The purpose of Stage 1 **Screening** is not to compare intersection alternatives against each other but to assess the different intersection types individually to determine if and to what extent they **Decision** potentially meet the project purpose and need, strategic program goals and project context by answering a number of questions regarding intersection right-of-**Record** way, safety, context, operations and costs. After the Stage 1 analysis is complete, the ICAT Champion will review and verify the results prior to the user moving onto the Stage 2 alternative selection.

Stage 2: Stage 2 further analyzes intersection types selected from the Stage 1 screening and determines the best possible intersection type for the project needs. The **Alternative** Stage 2 analysis includes additional safety and operational analysis, environmental, utility, and right-of-way impacts, cost comparisons, and other factors specific **Decision** to the context. Once all data is entered, each alternative is scored and ranked, and results provided inform on the best intersection control(s). Once determined, **Record** the user will collaborate with the ICAT Champion to recommend the final solution. The ICAT Champion will review and verify the analysis results and the RTR

Intersections

- Provides information on all intersection types in tool
- Educational links – click on image to access published guides or research on each intersection



INTERSECTION CONTROL DESCRIPTIONS

Click on intersection images for additional resource publications

Signalized At-Grade Intersections



Signalized Intersection: The most common type of signalized intersection with high driver familiarity. Signal could be simple two-phase or more complex 8-phase to serve vehicular demand. Left turns can be permitted or protected (or combination of both). At a conventional 4-leg intersection there are 32 baseline conflict points.



Jughandle: Much like an at-grade diamond interchange, ramps on the major street diverge from the right side in advance of a cross street intersection, removing the left turn movement from directly at the cross-street intersection. Major street left turns are made at minor, stop-controlled intersections on the cross-street. Left turns from the cross-street remain as direct movements at the main intersection.




Median U-Turn: Left turn movements otherwise occurring at the main intersection are made via U-turns in the median, preceding or following right turns. U-turns may be only on major roadway or on both major and minor roadways. A conventional MUT has 16 baseline conflict points and has shown significant operational and safety benefits. Also known as: Indirect Left, Michigan Left, MUT



Continuous Green-T: Three-leg intersection that features raised channelization to allow the "top" through movement to operate under continual green. The opposite direction intersects with the major and minor street lefts at a signalized intersection (minor left turns merge with the continual through movement downstream). A Continuous Green-T has 9 baseline conflict points, the same as a conventional 3-leg.



Superstreet / Reduced Conflict Intersection: Similar to the Median U-turn but features break in cross-street traffic that allows signals on opposite directions to operate independently. Left turns can make direct turns onto the minor road but minor road thru and left turn movements are made using the directional U-turn crossovers. A Superstreet / RCI has 14 baseline conflict points (over 3 intersections).




Offset-T Intersection: The minor street is bifurcated at the major roadway at two T-intersections, whereas through movements on the minor roadway use a portion of the major street between intersections. The minor street can be either offset right (as pictured above) or offset left, and the intersections can be unsignalized or signalized. If signalized, proper signal coordination is essential for efficient

Intersection Data

Orange text or boxes
(drop-down selections)
are REQUIRED

Blue text or boxes
(drop-down selections)
are OPTIONAL



INTERSECTION CONTROL ASSESSMENT TOOL (ICAT) INTERSECTION DATA

Developed and Maintained in Cooperation with Georgia DOT CDOT ICAT Version 1.0 | Release Date: 8/30/2021

CDOT Project No: Requested by:

County: --County-- CDOT Region: --Region--

Major (State) Rd: Road 1 --typical section-- --ROW--
--Road Type-- --Intersection Turn Lanes-- --SL--

Minor (Crossing) Rd: Road 2 4-In divided, 28' median --ROW--
--Road Type-- --Intersection Turn Lanes-- --SL--

Major Rd Direction: --Direction-- Area Type: --Area Type--

Intersection Control: --Existing Control-- Terrain: --Terrain--

Prepared By: Date:

Project Description:

2021 Existing Volumes

		SB Road 1					
		#DIV/0!				0.00	
	(0)	(0)	(0)	(0)			
	0	0	0	0		0.0%	

Critical Lane V/C: 0.00

		2021 Intersection Daily Entering Volume (est): #DIV/0!					
	(0)	0	0	0	0	(0)	
	(0)	0	0	0	0	(0)	
	(0)	0	0	0	0	(0)	
	(0)	0	0	0	0	(0)	

0.0%

Roadway Volume Splits

Road 1: 50%
Road 2: 50%

2021 Opening Year Volumes

		SB Road 1					
		#DIV/0!				0.00	
	(0)	(0)	(0)	(0)			
	0	0	0	0		0.0%	

Critical Lane V/C: 0.00

		2021 Intersection Daily					
	(0)	0	0	0	0	(0)	
	(0)	0	0	0	0	(0)	
	(0)	0	0	0	0	(0)	
	(0)	0	0	0	0	(0)	

0.0%

VOLUME FACTOR DATA

Year	Existing Data Year *	Project Open Year
2021	Existing Data Year *	Project Open Year
2021	Existing Data Year *	Project Open Year

[ICAT Users Guide \(Double Click to Open\)](#)

[ICAT User Guide.pdf](#)

Existing Yr Volume Inputs

	EB Road 2			WB Road 2			NB Road 1			SB Road 1			Total
	LT	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT	
AM Peak Hr	0	0	0	0	0	0	0	0	0	0	0	0	0
PM Peak Hr	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)

Annual Growth Rate (% per yr): 0.0% 0.0% 0.0% 0.0%

Peak Hour Truck %: 0.0% 0.0% 0.0% 0.0%

AM (PM) Pedestrian Crossings: 0 (0) 0 (0) 30 (40) 0 (0)

--- IMPORTANT NOTE ---

ICAT is not an explicit Traffic Forecasting tool. Simple Open and Design Year volume projections are developed based on approach growth factors (entered above) and intersection K-factor**. If more detailed intersection volume forecasts are desired, tools such as TurnsW32 and/or NCHRP Report 255 methodology can be used independently and the results can be included using the Open and Design Year forecast override tables below.

Fill in below **BLUE TEXT** below ONLY if additional data is available; otherwise Opening & Design Year volumes are auto calculated based growth rate, K and D factors

Open Yr Volume Override

	EB Road 2			WB Road 2			NB Road 1			SB Road 1			Total
	LT	TH	RT	LT	TH	RT	LT	TH	RT	LT	TH	RT	
AM Peak Hr	0	0	0	0	0	0	0	0	0	0	0	0	0
PM Peak Hr	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)	(0)

Peak Hour Truck %: 0.0% 0.0% 0.0% 0.0%

AM (PM) Ped Crossings¹: 0 (0) 0 (0) 0 (0) 0 (0)

1: AM and (PM) pedestrian volumes crossings of each intersection leg (EB, WB, NB and SB), regardless of direction

Inputs in grey-shaded area
are outside print border

Case Study Example

- Not actual case study
 - Exercise meant to show functionality of tool
- Hwy 66 at Pace Street, City of Longmont CO
 - Signalized T-intersection
 - High-speed rural highway intersecting local collector



Intersection Data

- Input intersection, volume, crash data
- Project number and requested by
- County selection drop box and CDOT region
- Major and Minor Road data
 - Name (limit to 15 characters)
 - Typical section (most conservative) and ROW
 - Turn lanes (most conservative if different)
 - Speed limit
- Area type, current control, general terrain
- Preparer (agency/firm), date, project description
- Type of project (important to evaluation factors)

CDOT Project No:	12345	Requested by:	City of Longmont, CO
County:	Boulder	CDOT Region:	Region 4
Major (State) Rd:	CO-66 (UTE Hwy)	2-In undivided	120' ROW
	R-A Regional Hwy	Single LT and RT lanes	60 MPH
Minor (Crossing) Rd:	Pace Street	2-In undivided	80' ROW
	Other Local Road	Single LT and RT lanes	45 MPH
Major Rd Direction:	East/West	Area Type:	Suburban
Intersection Control:	Signalized Intersection	Terrain:	Rolling
Prepared By:	Region 4 Traffic Engineering	Date:	8/23/2021
Project Description:	ICAT Training Module		
Type of Project:	Safety Improvement Project		

Intersection Data

- Volume factor data
 - Existing, Opening and Design Year
 - Intersection K-factor
 - Used to generate volume forecasts
- Crash data
 - CDOT LOSS Total and Severity Score
 - PDO, injury & fatal crashes over 5 years

VOLUME FACTOR DATA

2021	Existing Data Year *
2023	Project Open Year
2043	Project Design Year

10%	K Factor**
-----	------------

* If current count data is older than 2016, collection of new (current) count data is recommended
 ** K Factor = proportion of average annual daily traffic occurring in the highest hour of the day

CRASH DATA:

Use DiExSys Data or LOSS Database to document number of PDO, injury, fatal crashes and LOSS at this intersection in past 5 years:


Use following link to access CDOT Crash Patterns/LOSS:
<https://cdot.maps.arcgis.com/apps/MapSeries/index.html?appid=3dd05bf3e7e746f5811f81ba6d13c5fe>

18	Number of PDO crashes in last 5 year period
6	Number of Injury crashes in last 5 year period
1	Number of Fatal crashes in last 5 year period
25	Total number of crashes in last 5 year period
4	LOSS Total
4	LOSS Severe

ICAT Users Guide
 (Double Click to Open)




ICAT User Guide.pdf



Intersection Data


- Existing AM (PM) volume data
- Annual growth rate on each approach
- Truck percentage on each approach
- Existing pedestrian crossing data (if available)
- Approach volumes, ADT's and future volume estimates appear in graphic
- ICAT not a traffic forecasting tool
 - Can import outside traffic forecast data
 - Will override calculated data



ICAT Stage I

Stage I – 15 Context Questions


- 15 questions related to ROW constraints, safety, road context, operations and maintenance and costs to understand intersection needs and context

 ICAT STAGE 1: ALTERNATIVE SHORT-LIST DECISION RECORD <small>Developed and Maintained in Cooperation with</small>		Right of Way			Safety			Roadway Context			Operations/Maintenance		Costs	Total Stage 1 Screening Evaluation Score		
Project Number:	0012345	Q1: Is ROW on major road constrained? (0=no, 1=somewhat, 2=highly)	Q2: Is ROW on minor road constrained? (0=no, 1=somewhat, 2=highly)	Q3: Intersection quadrants constrained? (0=no, 1=somewhat, 2=highly)	Q4: Are there intersection safety issues? (0=low, 1=moderate, 2=crash hot spot)	Q5: Are there significant pedestrian crossings? (0=none/low, 1=moderate, 2=high)	Q6: Is there significant bicycle activity? (0=none/low, 1=moderate, 2=high)	Q7: Are one or more approach speeds high? (0=no, 1=moderate, 2=high)	Q8: Do roadway contexts, characteristics transition at intersection? (0=no, 1=yes)	Q9: Are there numerous driveways near intersection? (0=no, 1=few, 2=many)	Q10: What is adjacent intersection spacing? (0=isolated, 1=network, 2=dense network)	Q11: Is this a T-intersection? Or can minor ST thru or left turns be eliminated? (0=No, 2=Yes)	Q12: Are design yr no-build volumes high? No-Build 2043 V/C=1.16; (0=low, 2=mod, 4=high)		Q13: Are exist LT volumes high? (Max 2021 LT =270 vph) ; (0=no, 1=somewhat, 2=yes)	Q14: Could intersection become interchange in next 20 yrs? (0=no, 1=maybe, 2=probably)
Project Location:	CO-66 (UTE Hwy) @ Pace Street															
Existing Control:	Signalized Intersection															
Prepared by:	Region 4 Traffic Engineering															
Date:	8/23/2021															
1	Answer questions 1-16 with rating of 0, 1 or 2.	1	0	0	2	1	1	2	0	0	1	2	1	0	1	
2	Deselect or select any alternative by placing an X or Y (respectively) in column to right of score; Enter change justification in rightmost column															
Intersection Alternatives: (see Intersections tab for detailed description of intersection/interchange type)																

Q1: Is ROW on major road constrained? (0=no, 1=somewhat, 2=highly)
Q2: Is ROW on minor road constrained? (0=no, 1=somewhat, 2=highly)
Q3: Intersection quadrants constrained? (0=no, 1=somewhat, 2=highly)
Q4: Are there intersection safety issues? (0=low, 1=moderate, 2=crash hot spot)
Q5: Are there significant pedestrian crossings? (0=none/low, 1=moderate, 2=high)
Q6: Is there significant bicycle activity? (0=none/low, 1=moderate, 2=high)
Q7: Are one or more approach speeds high? (0=no, 1=moderate, 2=high)
Q8: Do roadway contexts, characteristics transition at intersection? (0=no, 1=yes)
Q9: Are there numerous driveways near intersection? (0=no, 1=few, 2=many)
Q10: What is adjacent intersection spacing? (0=isolated, 1=network, 2=dense network)
Q11: Is this a T-intersection? Or can minor ST thru or left turns be eliminated? (0=No, 1=Yes)
Q12: Are design yr no-build volumes high? No-Build 2043 V/C=1.65; (0=low, 2=mod, 4=high)
Q13: Are exist LT volumes high? (Max 2021 LT =400 vph) ; (0=no, 1=somewhat, 2=yes)
Q14: Could intersection become interchange in next 20 yrs? (0=no, 1=maybe, 2=probably)
Q15: Are costs a primary decision factor? (0=no, 1=somewhat, 2=yes)


Stage I – 15 Context Questions

- 15 questions related to ROW constraints, safety, road context, operations and maintenance and costs to understand intersection needs and context

 ICAT STAGE 1: ALTERNATIVE SHORT-LIST DECISION RECORD <small>Developed and Maintained in Cooperation with</small>		Right of Way			Safety			Roadway Context			Operations/Maintenance		Costs	Total Stage 1 Screening Evaluation Score		
Project Number:	0012345	Q1: Is ROW on major road constrained? (0=no, 1=somewhat, 2=highly)	Q2: Is ROW on minor road constrained? (0=no, 1=somewhat, 2=highly)	Q3: Intersection quadrants constrained? (0=no, 1=somewhat, 2=highly)	Q4: Are there intersection safety issues? (0=low, 1=moderate, 2=crash hot spot)	Q5: Are there significant pedestrian crossings? (0=none/low, 1=moderate, 2=high)	Q6: Is there significant bicycle activity? (0=none/low, 1=moderate, 2=high)	Q7: Are one or more approach speeds high? (0=no, 1=moderate, 2=high)	Q8: Do roadway contexts, characteristics transition at intersection? (0=no, 1=yes)	Q9: Are there numerous driveways near intersection? (0=no, 1=few, 2=many)	Q10: What is adjacent intersection spacing? (0=isolated, 1=network, 2=dense network)	Q11: Is this a T-intersection? Or can minor ST thru or left turns be eliminated? (0=No, 2=Yes)	Q12: Are design yr no-build volumes high? No-Build 2043 V/C=1.16; (0=low, 2=mod, 4=high)		Q13: Are exist LT volumes high? (Max 2021 LT =270 vph); (0=no, 1=somewhat, 2=yes)	Q14: Could intersection become interchange in next 20 yrs? (0=no, 1=maybe, 2=probably)
Prepared by:	Region 4 Traffic Engineering															
Date:	8/23/2021															
1	Answer questions 1-16 with rating of 0, 1 or 2.															
2	Deselect or select any alternative by placing an X or Y (respectively) in column to right of score; Enter change justification in rightmost column															
Intersection Alternatives: (see Intersections tab for detailed description of intersection/interchange type)		1	0	0	2	1	1	2	0	0	1	2	2	1	0	1
		0														
		1														
		2														

Stage I – Shortlist Selection

- Overall intersection score determined
- Users can create conventional alternatives
- Select/deselect alternatives (with justification) in order to shortlist alternatives



Developed and Maintained in Cooperation with

ICAT STAGE 1: ALTERNATIVE SHORT-LIST DECISION RECORD

CDOT ICAT Version 1.0 | Release Date: 8/30/2021

Project Number: 0012345		Right of Way		Safety				Roadway Context				Operations/Maintenance		Costs		Total Stage 1 Screening Evaluation Score	Alternative choice override (justification required)	Use this Stage 1 assessment form to select 2 to 5 alternatives to be carried into Stage 2 evaluations; Intersection control alternatives with the highest total weighted scores will be highlighted in BLUE and automatically carried forward into the Stage 2 assessment worksheet.					
Project Location: Ute Hwy (CO-66) @ Pace Street		Q1: Is ROW on major road constrained? (0=no, 1=somewhat, 2=highly)	Q2: Is ROW on minor road constrained? (0=no, 1=somewhat, 2=highly)	Q3: Intersection quadrants constrained? (0=no, 1=somewhat, 2=highly)	Q4: Are there intersection safety issues? (0=no, 1=moderate, 2=crash hot spot)	Q5: Are there significant pedestrian crossings? (0=no/low, 1=moderate, 2=high)	Q6: Is there significant bicycle activity? (0=no/low, 1=moderate, 2=high)	Q7: Are one or more approach speeds high? (0=no, 1=moderate, 2=high)	Q8: Do roadway contexts, characteristics transition at intersection? (0=no, 1=yes)	Q9: Are there numerous driveways near intersection? (0=no, 1=few, 2=many)	Q10: What is adjacent intersection spacing? (0=isolated, 1=network, 2=dense network)	Q11: Is this a T-intersection? Or can minor ST thru or left turns be eliminated? (0=no, 2=yes)	Q12: Are design yr no-build volumes high? No-Build 2043 V/C=1.16; (0=low, 2=mod, 4=high)	Q13: Are exist LT volumes high? (Max 2021 LT =270 vph); (0=no, 1=somewhat, 2=yes)	Q14: Could intersection become interchange in next 20 yrs? (0=no, 1=maybe, 2=probably)				Q15: Are costs a primary decision factor? (0=no, 1=somewhat, 2=yes)	4	Scoring Override Justification:		
Existing Control: Signalized Intersection																							
Prepared by: Region 4 Traffic Engineering																							
Date: 8/12/2021																							
1	Answer questions 1-16 with rating of 0, 1 or 2.																						
2	Deselect or select any alternative by placing an X or Y (respectively) in column to right of score; Enter change justification in rightmost column																						
Intersection Alternatives: (see Intersections tab for detailed description of intersection/interchange type)		1	0	0	2	1	1	2	0	0	1	2	2	1	0	1							
Conventional Improvements	-- select --																						
	Minor Street Stop	2.00	2.00	3	1	1	3	2	0	0	3	2	0	0	0	3	22.0						
	All-Way Stop	2.00	2.00	3	3	1	2	1	1	0	1	2	0	0	0	3	21.0						
Unsignalized Intersections	Right-In/Right-out	2.00	2.00	3	3	2	2	2	0	0	3	3	0	-3	0	3	25.0						
	Right-in/Right-out/Left-in (3/4 access)	2.00	2.00	3	2	2	2	2	1	0	3	3	1	0	0	3	28.0						
	RIRO w/downstream U-Turn	1.48	2.00	1	3	2	2	2	1	-1	2	2	0	0	0	2	23.5						
	Mini Roundabout	2.00	2.00	3	2	1	2	1	2	-1	2	3	0	1	0	3	23.0						
	Single Lane Roundabout	2.00	2.00	2	3	1	2	2	3	-1	2	3	1	2	0	2	29.0						
	Multilane Roundabout	2.00	2.00	1	2	1	1	1	3	-2	1	2	2	3	1	1	23.0						
	RCUT / J-Turn (stop control)	1.48	2.00	1	2	2	2	2	2	-1	2	2	1	2	1	3	26.5						
	High-T (unsignalized)	2.00	2.00	3	1	0	1	2	1	-2	0	6	1	0	0	2	25.0						
	Unsignalized Offset-T Intersection	2.00	2.00	3	1	1	2	2	2	-1	0	4	1	1	0	2	24.0						
	Other Signalized Intersection (Describe)																						
Signalized Intersections	Signalized Intersection	2.00	2.00	3	2	2	2	2	1	-1	2	2	2	2	0	2	28.0						
	Median U-Turn	1.48	2.00	1	2	2	3	3	1	-1	2	-1	3	1	3	1	24.5						
	Superstreet / RCI	1.48	2.00	1	2	2	3	3	1	-1	2	2	3	2	3	1	31.5						
	Displaced Left-Turn / CFI	1.42	1.67	0	1	0	1	2	1	-2	0	1	3	3	0	0	19.4						
	Continuous Green-T	2.00	2.00	3	1	0	2	2	1	-2	0	6	2	2	0	2	30.0						
	Signalized Offset-T Intersection	2.00	2.00	3	1	1	2	2	2	-1	3	2	2	2	1	2	26.0						
	Jughandle	2.00	1.88	0	1	1	2	3	1	-2	0	0	3	1	3	0	20.0						

Introduction
Intersections
IntersectionData
Stage1
Costs
Stage2
Scoring
Clearinghouse
Env

⏪
⏩
⏴
⏵

Note: If No-Build Condition is a desired alternative to evaluate, place a "Y" in the *alternative choice override* column for the No-Build alternative and Enter "No-Build Condition" in the *Scoring Override Justification* column.

No-Build Condition:

Signalized Intersection

Exclude from Selection? **No**

Conventional Improvements 1

Left Lanes **--select--**

Right Lanes **--select--**

Medians **--select--**

Control **--select--**

Conventional Improvements 2

Left Lanes **--select--**

Right Lanes **--select--**


Medians **--select--**

Control **--select--**

Note: Any conventional improvements entered in table above are automatically selected as an alternative to assess (without a score given), no scoring override justification is required; if "Other" signalized or unsignalized intersection is described (written in), user must manually select as alternative ("Y") to advance.

Stage I – Shortlist Selection

- Overall intersection score determined
- Users can create conventional alternatives
- Select/deselect alternatives (with justification) in order to shortlist alternatives

ICAT STAGE 1: ALTERNATIVE SHORT-LIST DECISION RECORD																																					
 Developed and Maintained in Cooperation with														CDOT ICAT Version 1.0 Release Date: 8/30/2021																							
Project Number:		0012345																																			
Project Location:		Ute Hwy (CO-66) @ Pace Street																																			
Existing Control:		Signalized Intersection																																			
Prepared by:		Region 4 Traffic Engineering																																			
Date:		8/12/2021																																			
1 Answer questions 1-16 with rating of 0, 1 or 2. 2 Deselect or select any alternative by placing an X or Y (respectively) in column to right of score; Enter change justification in rightmost column		Right of Way Q1: Is ROW on major road constrained? (0=no, 1=somewhat, 2=highly) Q2: Is ROW on minor road constrained? (0=no, 1=somewhat, 2=highly) Q3: Intersection quadrants constrained? (0=no, 1=somewhat, 2=highly)		Safety Q4: Are there intersection safety issues? (0=low, 1=moderate, 2=crash hot spot crossings?) Q5: Are there significant pedestrian crossings? (0=none/low, 1=moderate, 2=high) Q6: Is there significant bicycle activity? (0=none/low, 1=moderate, 2=high)				Roadway Context Q7: Are one or more approach speeds high? (0=no, 1=moderate, 2=high) Q8: Do roadway contexts, characteristics transition at intersection? (0=no, 1=yes) Q9: Are there numerous driveways near intersection? (0=no, 1=few, 2=many)				Operations/Maintenance Q10: What is adjacent intersection spacing? (0=isolated, 1=network, 2=dense network) Q11: Is this a T-intersection? Or can minor ST thru or left turns be eliminated? (0=no, 2=yes)			Costs Q12: Are design yr no-build volumes high? No-Build 2043 V/C=1.16; (0=low, 2=mod, 4=high) Q13: Are exist LT volumes high? (Max 2021 LT =270 vph); (0=no, 1=somewhat, 2=yes) Q14: Could intersection become interchange in next 20 yrs? (0=no, 1=maybe, 2=probably) Q15: Are costs a primary decision factor? (0=no, 1=somewhat, 2=yes)			Total Stage 1 Screening Evaluation Score Alternative choice override (justification required)		Use this Stage 1 assessment form to select 2 to 5 alternatives to be carried into Stage 2 evaluations; Intersection control alternatives with the highest total weighted scores will be highlighted in BLUE and automatically carried forward into the Stage 2 assessment worksheet.																	
		Intersection Alternatives: (see Intersections tab for detailed description of intersection/interchange type)		1		0		0		2		1		1		2		0		0		1		2		2		1		0		1		Number of Alternatives to be Evaluated in Stage 2: 4		Scoring Override Justification:	
Conventional Improvements		Medians, Add FYA																														Y Low-cost alternative		Exclude from Selection? No			
		-- select --																														Conventional Improvements 1		Left Lanes --select-- Right Lanes --select-- Medians Add Median on Ute Hwy (CO-66) Control Add FYA			
Unsignalized Intersections		Minor Street Stop		2.00		2.00		3		1		1		3		2		0		0		3		2		0		0		3		22.0					
		All-Way Stop		2.00		2.00		3		3		1		2		1		1		0		1		2		0		0		3		21.0					
		Right-In/Right-out		2.00		2.00		3		3		2		2		2		0		0		3		3		0		-3		0		3		25.0			
		Right-in/Right-out/Left-in (3/4 access)		2.00		2.00		3		2		2		2		2		1		0		3		3		1		0		0		3		28.0			
		RIRO w/downstream U-Turn		1.48		2.00		1		3		2		2		2		1		-1		2		2		0		0		0		2		23.5			
		Mini Roundabout		2.00		2.00		3		2		1		2		1		2		-1		2		3		0		1		0		3		23.0			
		Single Lane Roundabout		2.00		2.00		2		3		1		2		2		3		-1		2		3		1		2		0		2		29.0		X Does not provide for CO-66 widening	
		Multilane Roundabout		2.00		2.00		1		2		1		1		1		3		-2		1		2		2		3		1		1		23.0		Y Higher RAB capacity; allows widening	
		RCUT / J-Turn (stop control)		1.48		2.00		1		2		2		2		2		2		-1		2		2		1		2		1		3		26.5			
		High-T (unsignalized)		2.00		2.00		3		1		0		1		2		1		-2		0		6		1		0		0		2		25.0			
		Unsignalized Offset-T Intersection		2.00		2.00		3		1		1		2		2		2		-1		0		4		1		1		0		2		24.0			
		Other Signalized Intersection (Describe)																																			
Signalized Intersections		Signalized Intersection		2.00		2.00		3		2		2		2		2		1		-1		2		2		2		2		0		2		28.0			
		Median U-Turn		1.48		2.00		1		2		2		3		3		1		-1		2		-1		3		1		3		1		24.5			
		Superstreet / RCI		1.48		2.00		1		2		2		3		3		1		-1		2		2		3		2		3		1		31.5			
		Displaced Left-Turn / CFI		1.42		1.67		0		1		0		1		2		1		-2		0		1		3		3		0		0		19.4			
		Continuous Green-T		2.00		2.00		3		1		0		2		2		1		-2		0		6		2		2		0		2		30.0			
		Signalized Offset-T Intersection		2.00		2.00		3		1		1		2		2		2		-1		3		2		2		2		1		2		26.0			
		Jughandle		2.00		1.88		0		1		1		2		3		1		-2		0		0		3		1		3		0		20.0			

Note: If No-Build Condition is a desired alternative to evaluate, place a "Y" in the alternative choice override column for the No-Build alternative and Enter "No-Build Condition" in the Scoring Override Justification column.

No-Build Condition:

Signalized Intersection

Exclude from Selection?

No

Conventional Improvements 1

Left Lanes

--select--

Right Lanes

--select--

Medians

Add Median on Ute Hwy (CO-66)

Control

Add FYA

Conventional Improvements 2

Left Lanes

--select--

Right Lanes

--select--

Medians

--select--

Control


--select--

Note: Any conventional improvements entered in table above are automatically selected as an alternative to assess (without a score given), no scoring override justification is required; if "Other" signalized or unsignalized intersection is described (written in), user must manually select as alternative ("Y") to advance.

ICAT Cost Worksheets (Optional)

Costs Worksheet

- Optional to aid cost development
- Existing conditions data
- Alternative Specific Data
 - Utility, driveway impacts
 - Wall, bridge area
 - Additional ROW & landscape costs
- Site Conditions
 - ROW, drainage type
 - Sidewalk/bike/MUP facilities
 - Project size / traffic management
 - Design/contingency factors



INTERSECTION CONTROL ASSESSMENT TOOL (ICAT): COST ESTIMATING AID

CDOT ICAT Version 1.0 | Release Date: 9/17/2021

Location: Ute Hwy (CO-66) @ Pace Street

Existing Intersection Control: Signalized Intersection

Type of Project: Safety Improvement Project

County: Boulder

CDOT Region: Region 4

Area Type: Suburban

Date: 8/23/2021

Agency/Firm: Region 4 Traffic Engineer

CDOT Proj No: 0012345

Movement	EB Ute Hwy (CO-66)			WB Ute Hwy (CO-66)			NB Pace Street			SB Pace Street		
	Left Turn	Thru	Right Turn	Left Turn	Thru	Right Turn	Left Turn	Thru	Right Turn	Left Turn	Thru	Right Turn
Number of Lanes	0	1	1	1	1	0	1	0	1	0	0	0
Bay Length**	0'		400'	750'		0'	220'		0'	0'		0'
Median Width (if any)		0'			0'			0'			0'	
Right-of-Way	120'			120'			80'			80'		

Alternative	Pavement Area	Utility Impacts	Driveways Impacted	Retaining Wall (sqft)	New/Widen Bridge (sqft)	Add'l ROW/ Demolition	Landscape Cost
Multilane Roundabout	38112 sf	Moderate	0	200	0	\$0	\$30,000
Medians, Add FYA	0 sf	Minimal	0	0'	0	\$0	\$0
Superstreet / RCI	58000 sf	Moderate	2	500'	0	\$250,000	\$0
Continuous Green-T	38100 sf	Minimal	2	0'	0	\$0	\$0

Site Conditions

Prevalent ROW Type	Residential
ROW Cost/Acre	\$50,000
Topography	Rolling

Roadway

Drainage	Standard ditch
Sidewalks	SW on Maj & Min (both)
Bike Lanes / MU Paths	10' MU path on major

Intersection

Signal Poles	Mast Arm
Project Size	Single intersection
Traffic Management	Maintain Traffic

Factors

Engineering Design	20%
Contingency	30%

Environmental Impacts	Multilane Roundabout	Medians, Add FYA	Superstreet / RCI	Continuous Green-T
Historic District/Property:	\$0	\$0	\$0	\$0
Archaeology Resources:	\$0	\$0	\$0	\$0
Graveyard:	\$0	\$0	\$0	\$0
Stream:	\$0	\$0	\$0	\$0
UST/Hazmat:	\$0	\$0	\$0	\$0
Park Land:	\$0	\$0	\$0	\$0
EJ Community:	\$0	\$0	\$0	\$0
Floodplain:	\$0	\$0	\$0	\$0
Wetland:	\$0	\$0	\$0	\$0
T&E Species Habitat:	\$0	\$0	\$0	\$0
Totals:	\$0	\$0	\$0	\$0

NOTES:

For minimal or significant environmental impacts identified in Stage 2 (highlighted in ORANGE), enter cost estimate to mitigate each impact.

Costs Worksheet

- Alternative specific factors chosen to better define costs
- Examples include:
 - Pavement improvement type
 - Roundabout diameter
 - U-turn crossover distances
 - Adding turn lanes
 - Intersection spacing
 - Median openings
 - Median treatments
 - Lane channelization
 - Special signing and marking

Control Alternative	Baseline Alternative Description	Criteria 1	Criteria 2	Criteria 3
Mini Roundabout	New mini RND w/splitter islands, paved (traversable) center island	70' Inscribed Dia (default mini)	1 RT by-pass lane	
Single Lane Roundabout	New single lane RND w/splitter islands, truck apron and landscaped median	130' Inscribed Dia (default single)	No RT by-pass lanes	
Multilane Roundabout	New multi-lane RND w/splitter islands, truck apron and landscaped median	180' Inscribed Dia (default multi)	No RT by-pass lanes	2x1 Multilane RND
RCUT / J-Turn (stop control)	Add directional U-turns, left turn channelization, restrict turns from minor Street	50' Inscribed Diameter 70' Inscribed Dia (default m)	Avg 600' U-turn spacing (Default)	2 new directional openings
High-T (unsignalized)	Separate through lane from left turn traffic w/downstream merge condition	90' Inscribed Diameter 110' Inscribed Diameter 130' Inscribed Dia (default s)	3' raised median separator	Convert existing LT lane
Unsignalized Offset-T Intersection	Separate intersection legs into two T-intersections	150' Inscribed Diameter 180' Inscribed Dia (default r)	Offset left / right intersection	500' intersection spacing (Default)
Other Signalized Intersection (Describe)	Cost estimate not available	200' Inscribed Diameter		
Signalized Intersection	Signalize existing intersection	Resurface intersection	Add left lanes on Both	No new right turn lanes
Median U-Turn	Add directional U-turns on Main Road; signalize crossovers	New full depth pavement	Avg 600' U-turn spacing (Default)	2 new directional openings
Superstreet / RCI	Add directional U-turns on Main Road; signalize main intersection and crossovers; RT only from Minor Road	Resurface intersection	Avg 800' U-turn spacing	2 new directional openings
Displaced Left-Turn / CFI	Right turn bypass lanes; signalized main and crossover intersections	Resurface intersection	Avg 600' crossover spacing (Default)	Two-leg CFI (crossovers on Main)
Continuous Green-T	Single through lane on high side	Resurface intersection	4' raised median separator	Convert existing LT lane
Signalized Offset-T	Separate intersection legs into two T-intersections	New full depth	Offset left / right	500' intersection spacing (Default)

ICAT Stage II

Stage II



- Evaluation of 5 Factors:
 - Costs
 - Traffic Operations
 - Safety
 - Environmental Impacts
 - Stakeholder Input
- Cost data from Cost worksheet
 - Generates costs for each alternative
 - Can adjust cost specifics
- Traffic analysis measures
 - No-build design year operations
 - Delay, V/C for each alternative

ICAT STAGE 2: ALTERNATIVE SELECTION DECISION RECORD									
CDOT		Developed and Maintained in Cooperation with Georgia DOT						CDOT ICAT Version 1.0 Release D	
CDOT Project Number: 0012345		Existing / Design Year No-Build Traffic Operations							
Project Location: CO-66 (UTE Hwy) @ Pace Street		Traffic Analysis Measure of Effectiveness						Intersection Delay	
Existing Intersection Control: Signalized Intersection		Traffic Analysis Software Used						Synchro 10	
County/Region: Boulder / CDOT Region 4		Analysis Time Period						AM Peak Hr	PM Peak Hr
Area Type: Suburban		2021 Existing No-Build Peak Hr Intersection Delay						40.0 sec	52.0 sec
Prepared by: Region 4 Traffic Engineering		2021 Existing No-Build Peak Hr Intersection V/C ratio						0.80	0.90
Date: 8/23/2021		2043 Design Yr No-Build Peak Hr Intersection Delay						64.0 sec	82.0 sec
Type of Project: Safety Improvement Project		2043 Design Yr No-Build Peak Hr Intersection V/C ratio						1.10	1.25
Alternatives Analysis		Alternative 1		Alternative 2		Alternative 3		Alternative 4	
Proposed Control Type Improvement:		Multilane Roundabout		Medians, Add FYA		Superstreet / RCI		Continuous Green-T	
Project Cost (From Cost Worksheet)		Add add'l description here		Add add'l description here		Add add'l description here		Add add'l description here	
Construction Cost		\$1,439,400		\$450,000		\$1,403,215		\$673,383	
ROW Cost		\$0		\$0		\$283,058		\$0	
Environmental Cost		\$0		\$0		\$0		\$0	
Reimbursable Utility Cost		\$51,321		\$40,000		\$70,161		\$20,202	
Design & Contingency Cost		\$513,215		\$240,000		\$701,608		\$336,692	
Cost Adjustment (justification req'd)		0%		0%		0%		0%	
Total Cost		\$2,003,936		\$730,000		\$2,458,042		\$1,030,277	
Traffic Operations		SIDRA 7		Synchro 10		Synchro 10		Synchro 10	
Traffic Analysis Software Used		AM Peak Hr PM Peak Hr		AM Peak Hr PM Peak Hr		AM Peak Hr PM Peak Hr		AM Peak Hr PM Peak Hr	
Analysis Period		AM Peak Hr PM Peak Hr		AM Peak Hr PM Peak Hr		AM Peak Hr PM Peak Hr		AM Peak Hr PM Peak Hr	
2043 Design Yr Build Intersection Delay		30.0 sec 35.0 sec		55.0 sec 66.0 sec		40.0 sec 48.0 sec		24.0 sec 53.0 sec	
2043 Design Yr Build Intersection V/C		0.65 0.70		0.95 1.10		0.70 0.90		0.55 0.98	

Stage II: Safety

- Safety benefit by change of intersection control determined using FHWA's CMF Clearinghouse (www.cmfclearinghouse.org)
 - CMFs (Crash Modification Factor) used to compute the expected number of crashes after implementing a given improvement
 - CRFs (Crash Reduction Factors) estimates % reduction in crashes
- Many CMFs predefined based on existing/proposed control; for some, users may have to find or develop and document



The screenshot shows the CMF Clearinghouse website. At the top, there is a navigation bar with links for "Skip to main content", "Site Map", "Notice", "Sign Up for our e-Newsletter", and "Home". Below this is a secondary navigation bar with links for "About the CMF Clearinghouse", "Using CMFs", "Developing CMFs", and "Additional Resources". The main content area features a search interface on the left with a "Search for:" field containing "Roundabout", an "in" dropdown menu set to "Countermeasure Name", and a "Search CMFs" button. To the right of the search interface is a featured article titled "Get training on applying CMFs" with a sub-headline "Find out about two CMF-related trainings offered through the National Highway Institute, *Application of Crash Modification Factors and Science of Crash Modification Factors*". Below the search interface is a dark blue box with white text explaining that a CMF is used to compute the expected number of crashes after implementing a countermeasure. To the right of this box is a "Recently Added CMFs" section listing three items: "Install bicycle lanes" (CMF: 0.77), "Convert diamond interchange to Diverging Diamond Interchange", and "Improve angle of channelized right turn lane".

Stage II

- Safety data from CMF Clearinghouse or added from other data sources
- Identify any potential environmental impacts for each alternative
- *Environmental Impacts* worksheet used to identify mitigation efforts; add mitigation costs to *Cost* worksheet

Safety Analysis				
Predefined CRF: PDO	26%	0%	15%	4%
Predefined CRF: Fatal/Inj	71%	0%	15%	4%
Predefined CRF Source:	FHWA Clearinghouse IDs: 4196 / 4195	-	FHWA Clearinghouse ID:9984	CDOT Study ID:8655
User Defined CRF: PDO		8%		
User Defined CRF: Fatal/Inj		8%		
User Defined CRF Source (write in if applicable):		CDOT CMF Factor		
Environmental Impacts				
Historic District/Property:	None	None	None	None
Archaeology Resources:	None	None	None	None
Graveyard:	None	None	None	None
Stream:	Minimal	None	None	None
UST/Hazmat:	None	None	None	None
Park Land:	None	None	None	None
EJ Community:	None	None	None	None
Floodplain:	None	None	None	None
Wetland:	None	None	Significant	Minimal
T&E Species Habitat:	None	None	None	None

Stage II

- Stakeholder Inputs (if known)
 - Negative, neutral or supportive
 - Local Community Support
 - CDOT Region Support
- Final score and ranking and input of any comments

Proposed Control Type Improvement:	Multilane Roundabout	Medians,Add FYA	Superstreet / RCI	Continuous Green-T
Stakeholder Support:				
Local Community Support	Strong	Negative	Negative	Neutral
CDOT Region Support	Supportive	Negative	Supportive	Neutral
Final ICAT Stage 2 Score:	6.3	3.8	3.1	4.3
Rank of Control Type Alternatives:	1	3	4	2
Provide additional comments and/or explain any unique analysis inputs, or results (as necessary):	Multilane RAB is final selected alternative Design to provide for future fourth intersection leg			

Conclusions

- ICAT process is intended to:
 - Provide the optimal intersection solution
 - Document the data and approach used to select control choice
- Tool should NOT replace good engineering judgement
 - Use best judgment entering data
 - Lower scoring alternative can be selected (with justification) if scores are close
- CDOT will soon be issuing guidance on how and when to use ICAT
- Suggestions for improvements to the tool are welcome, and updates to ICAT are expected in future version releases
- Thank you and please visit the Learning Lane to view additional training videos, the ICAT worksheet and Users Guide